
### **DOUGHNUT AND CORNER BUMPERS**



### A-813 Doughnut

Commonly installed on the ends of tubular handles to give needed protection in manipulation of equipment. Note steel insert. Attached to wood with wood screws or to metal with rivets, bolts or metal screws. Weight: 6 oz. each.




## HOLES FOR 3/16" BOLTS 1-1/16" 75-80 Shore A

### A-833 Corner

Made to give adequate protection to all surfaces that may be contacted, such as doors, doorfacings, walls, furniture and other equipment. Easily attached by using self-tapping sheet metal screws.

Weight: 6 oz. each.






### A-1676 Corner

Made especially for use with A-567 Strip Bumper, giving a uniform continuous effect all around the equipment. Weight: 5 oz. each.






### A-2680 Corner

Made especially for use with A-1541 Strip Bumper, giving a uniform continuous effect all around the equipment. Weight: 5 oz. each.





### A-6926 Corner

Heavy duty corner bumper for maximum protection when equipment is used in warehouse or industrial environment.
Weight: 24 oz. each.



1//


### STRIP BUMPERS



Maximum Length 16'

### **Model A-2041**


Provides excellent protection for desk and table edges, etc. Maximum lengths 16 ft. for easy installation. Metal insert optional. Weight: 14 oz./ft.





### **Model 4925**


Molded strip corner bumper 12" long, for application to any right angle shape. Easily installed with self-tapping metal screws. Weight: 8 oz. each.





### Model A-1541


Popular small-sized strip bumper that is adaptable to many applications. This model is easily applied to equipment. Metal insert optional. Weight: 4 oz./ft.





### Model A-1019

Made especially for 1-1/4" commercial channel iron. Used for heavier type equipment where strength is necessary for operation. Gives that extra needed protection. Metal insert optional. Weight: 12 oz./ft.






### **Model A-4652**

Flat-based rubber strip bumper, with split top for easier installation.


Metal insert optional. Weight: 4 oz./ft.





### **Model A-2084**


Flat based rubber strip bumper designed for same use as A-567. With split top for easier installation. Metal insert optional. Weight: 9 oz./ft.





### Model A-567


Flat based rubber strip designed for installation on either metal or wood surfaces. Easily applied and does not require a special channel. Metal insert optional. Weight: 9 oz./ft.





Model A-6930

Designed for use with A-6929 corner bumper, this flat based rubber strip bumper gives added protection to outer perimeter of carts and equipment. Weight: 13 oz./ft.



Maximum Length 16'

### **ROUND TUBING**



3" OUTSIDE DIA.	INSIDE THICKNESS	OUTSIDE THICKNESS	PART NUMBER	
5/8" Dia. I.D.	15/16"	15/16"	A-8400	
3/4" Dia. I.D.	15/16"	15/16"	A-8401	
7/8" Dia. I.D.	15/16"	15/16"	A-8402	
1" Dia. I.D.	15/16"	15/16"	A-8403	
1-1/4" Dia. I.D.	15/16"	15/16"	A-8404	
WEIGHT: 3 OZ. EACH				
5" OUTSIDE DIA.	INSIDE THICKNESS	OUTSIDE THICKNESS	PART NUMBER	
1" Dia. I.D.	1-1/8"	5/8"	A-2270	
1-1/4" Dia. I.D.	1-1/8"	5/8"	A-2274	
1-1/2" Dia. I.D.	1-1/8"	5/8"	A-2275	
1.9" Dia. I.D.	1-1/8"	5/8"	A-2276	
WEIGHT: 12 OZ. EACH				

### **SQUARE TUBING**



3" OUTSIDE DIA.	INSIDE THICKNESS	OUTSIDE THICKNESS	PART NUMBER	
7/8" Dia. I.D.	15/16"	15/16"	A-8409	
1" Dia. I.D.	15/16"	15/16"	A-8410	
WEIGHT: 4 OZ. EACH				
5" OUTSIDE DIA.	INSIDE THICKNESS	OUTSIDE THICKNESS	PART NUMBER	
1" Dia. I.D.	1-13/16"	5/8"	A-7668	
1-1/4" Dia. I.D.	1-13/16"	5/8"	A-4953	
1-1/2" Dia. I.D.	1-13/16"	5/8"	A-2272	
1-5/8" Dia. I.D.	1-13/16"	5/8"	A-5375	
1-3/4" Dia. I.D.	1-13/16"	5/8"	A-6147	
2" Dia. I.D.	1-13/16"	5/8"	A-2273	
WEIGHT: 12 OZ. EACH				

### REVOLVING



These revolving bumpers are designed to fit on a caster stem and prevent the bed or other article of furniture on which they are used from striking the wall. The bumper will strike the wall first and, if the bed is moved along the wall, the bumper will revolve, thus eliminating any chance of smearing the wall or causing an erasure. Made from grey non-marking rubber. When ordering revolving bumpers, specify bore size.

4" OUTSIDE DIA.	WEIGHT	PART NUMBER
3/8" Wide Face	8 oz. each	A-6478
5" OUTSIDE DIA.	WEIGHT	PART NUMBER

### **MOLD-ON HEAVY DUTY RUBBER**



Designed to fit almost every type of portable equipment requiring heavy duty bumpers. These solid rubber bumpers with a heavy steel insert are made of grey non-marking rubber, molded around the steel insert making the entire unit virtually indestructible and long lasting. The machine steel hubs are made in the following sizes: 7/16", 1/2", 9/16", 5/8", 3/4", 13/16", 7/8" and 1". Other sizes available on request.

DIAMETER IN INCHES	WEIGHT	PART NUMBER
4"	5 oz. each	A-4940
5"	12 oz. each	A-4941
7-1/2"	28 oz. each	A-4820
8-1/2"	42 oz. each	B-6487

146

### 4714-01 (Black)

# B-3-1/2 R (Round Stem) B-3-1/2 S (Square Stem)



### **End Bumper B-1**

Grey or black end bumper generally used on the ends of tubular handles on carts and platform trucks. Designed to help protect equipment as well as walls and door facings. Bumper Dimensions: 3-1/4" diameter with steel insert for 5/16" mounting bolt.

### **Tubing Bumper B-3-1/2**

Designed to fit over 1" OD round or square tubing on carts and a variety of rolling equipment. Please specify round or square tubing when ordering. Specify **B-3-1/2 R** for round ID and **B-3-1/2 S** for square ID.

### **Rolling Bumper B-5**

5" diameter rolling bumper; tapered grey rubber bonded to zinc plated insert with removable center bushings to fit stem diameters from 3/8" to 1-1/8". Specify bumper **B-5**.



### Corner Bumper B-8

Grey or black corner bumper for mounting on the corners of equipment, carts or any flat surfaces. Absorbs shock to protect equipment and walls, doors and furniture. Bumper Dimensions: 7/8" thick x 1" high x 2-5/8" long from inside corner on each side.



### **Corner Bumper B-10**

A heavy duty bumper with reinforced, rounded corner to protect equipment from shocks and bumps. Steel inserts inside bumper assures permanent mounting to equipment. Ends are tapered and rounded for added design appeal. Bumper Dimensions: 1" thick x 1-1/16" high x 3-1/16" long from inside corner on each side. Mounting holes are 13/64" diameter.



### **Corner Bumper B-12**

A common bumper used to protect a wide variety of mobile equipment and the surrounding environment from bumps and scrapes. This bumper is equipped with steel inserts and can be mounted on any flat surface. The ends of the bumper legs may be cut at notched area to make square ends. Bumper features steel inserts. Bumper Dimensions: 7/8" thick x 1" high x 3-1/8" long from inside corner on each side. **Grey bumper with no steel insert, order model number 4724-30.**