

# PC

## Prestige™ High Impact Polymer Casters




New Prestige™ casters are designed with high impact glass-filled nylon. Perfect for washdowns or corrosive environments.

### TYPICAL APPLICATIONS

- Hotel equipment
- Institutional equipment
- Display racks and cases
- Stock carts
- Laundry trucks

### MOUNTING OPTIONS



**Threaded Stem:** 1/2" - 13 x 1  
**Grip Ring Stem:** 27/32" Diameter x 23/16"

### FEATURES

- Swivel Section: Precision ball raceway
- Axle: 3/8" diameter
- Finish: Beige plastic to resist rust and corrosion
- Alternate or custom caster configurations available

### BRAKE OPTIONS


**Total Lock**  
specify T

See charts below to order



### BEARING

Delrin (51)



### Top Plate Polyurethane on Polypropylene (51 Delrin Bearing)

Swivel Top Plate  
 5 | 1 1/4 | 300 | 6 7/8 | 1 5/16 | 2 3/4 | **PCXA05051S**

Swivel Top Plate with Total Lock Brake  
 5 | 1 1/4 | 300 | 6 7/8 | 1 5/16 | 2 3/4 | **PCXA05051ST**

**XA** Prevenz™ antimicrobial models available. Add PREV to end of caster number.

### Threaded Stem Polyurethane on Polypropylene (51 Delrin Bearing)

Threaded Stem  
 5 | 1 1/4 | 300 | 6 1/2 | 1 5/16 | 2 3/4 | **PCXA05051S-S52**

Threaded Stem with Total Lock Brake  
 5 | 1 1/4 | 300 | 6 1/2 | 1 5/16 | 2 3/4 | **PCXA05051ST-S52**

**XA** Prevenz™ antimicrobial models available. Add PREV to end of caster number.

### Grip Ring Polyurethane on Polypropylene (51 Delrin Bearing)

Grip Ring Stem  
 5 | 1 1/4 | 300 | 6 1/2 | 1 5/16 | 2 3/4 | **PCXA05051S-S54**

Grip Ring with Total Lock Brake  
 5 | 1 1/4 | 300 | 6 1/2 | 1 5/16 | 2 3/4 | **PCXA05051ST-S54**

**XA** Prevenz™ antimicrobial models available. Add PREV to end of caster number.

### Prevenz™ Antimicrobial Wheels

The EPA registered and FDA compliant antimicrobial additive used in Prevenz™ wheels is designed to suppress the growth of a variety of destructive and odor causing microbes including bacteria, molds, mildew and fungi. These wheels are suitable for a variety of applications including medical equipment, food equipment, pharmaceutical, chemical, meat & poultry, processing plants and more. To order add "PREV" to end of caster number.



**XA Prevenz™**  
Polyurethane on  
Polypropylene

# Product Numbering System

## CASTERS

16PD06201S is a 16 Series 6" x 2" swivel top plate caster with Polyurethane/Aluminum core wheel and straight roller bearing. See below for caster number breakdown.

|                                     |   |                                    |   |   |   |
|-------------------------------------|---|------------------------------------|---|---|---|
| <b>16</b>                           | <b>PD</b>   | <b>06</b>                          | <b>2</b>  | <b>01</b>   | <b>S</b>  |
|                                     |   |                                    |   |   |   |
| <b>Caster Series</b><br>(16 Series) | <b>Wheel Code</b><br>(PD is Polyurethane on aluminum core) (see Wheel Section for codes, page 147 to 193) | <b>Diameter Code</b><br>(06 is 6") | <b>Tread Width Code</b><br>(2 is 2")<br>0: Less than 1-1/2<br>1: 1-1/2 to 1-5/8<br>2: 1-3/4 to 2<br>3: 2-1/8 to 2-7/16<br>4: 2-1/2 to 2-3/4<br>5: 2.8 to 3-3/8<br>6: 3-1/2 to 3-7/8<br>7: 4 to 4-7/8<br>8: 5 to 5-1/2<br>9: Over 5-1/2<br>X: 3-1/2 Dia. Wheel | <b>Bearing Code</b><br>(01 is Straight Roller Bearing) (see Bearing Section for codes, page 13) | <b>Swivel/Rigid Code</b><br>(S is swivel, R is rigid) |

## OPTIONAL FEATURES

To be listed under the caster model number when ordering. Note: Some brake and swivel lock options are now placed at the end of the part number. Please see individual series for option designation.

|   |   |
|---|---|
| <b>CB</b>                                     | <b>16</b>   |
|   |   |
| <b>Option Code</b><br>(CB is cam style brake) | <b>Option Code</b><br>(In this case cam style brake for 16 series caster) |

## WHEELS

PD0620112 is a 6" x 2" Polyurethane/Aluminum core with 3/4" straight roller bearing.

|   |                                    |  |   |  |
|---|------------------------------------|--|---|--|
| <b>PD</b>   | <b>06</b>                          | <b>2</b>   | <b>01</b>   | <b>12</b>  |
|   |                                    |  |   |  |
| <b>Wheel Code</b><br>(PD is Polyurethane on aluminum core) (see Wheel Section for codes, page 147 to 193) | <b>Diameter Code</b><br>(06 is 6") | <b>Tread Width Code</b><br>(2 is 2")<br>0: Less than 1-1/2<br>1: 1-1/2 to 1-5/8<br>X: 1-1/4" tread width for 3-1/2" Dia. Wheels<br>2: 1-3/4 to 2<br>3: 2-1/8 to 2-7/16<br>4: 2-1/2 to 2-3/4<br>5: 2.8 to 3-3/8<br>6: 3-1/2 to 3-7/8<br>7: 4 to 4-7/8<br>8: 5 to 5-1/2<br>9: Over 5-1/2 | <b>Bearing Code</b><br>(01 is Straight Roller Bearing) (see Bearing Section for codes, page 13)<br><br>Note: for wheel less bearing order 41 or 00 depending on wheel--see wheel section pages 147-193) | <b>Bearing ID Code</b><br>(12 is 3/4")<br>Bearing I.D. for wheels with bearing. Wheel bore I.D. for wheels less bearing. In 1/16" increments, for example:<br>12 divided by 16 or 3/4"<br>Common Bore Sizes:<br>19 = 1-3/16<br>31 = 1-15/16<br>39 = 2-7/16 |

## RIGS

16YA06201S is a Medium-heavy duty swivel rig that would accommodate the above 6" x 2" PD wheel.

|                                     |   |                                    |   |  |   |
|-------------------------------------|---|------------------------------------|---|--|---|
| <b>16</b>                           | <b>YA</b>   | <b>06</b>                          | <b>2</b>  | <b>01</b>  | <b>S</b>  |
|                                     |   |                                    |   |  |   |
| <b>Caster Series</b><br>(16 Series) | <b>Rig Code</b><br>(YA is rig only designation)<br>YA: Standard<br>YB: Moldon Lead<br>YJ: Ball Load<br>YN: Semi-Pneumatic<br>YO: Full Pneumatic<br>(Note: not all options included) | <b>Diameter Code</b><br>(06 is 6") | <b>Inside Leg Spacing Code</b><br>(2 means that rig fits 1-3/4" to 2" tread width wheel)<br><br>See <b>Tread Width Code</b> in <b>WHEELS</b> above. | <b>Axle/Nut Code</b><br>(01 indicates Stripped rig, no parts)<br>00: Rig comes with axle, nut, spanner and thrust washers<br>03: Complete with axle and nut. | <b>Swivel/Rigid Code</b><br>(S is swivel, R is rigid) |