

FEATURES

Load Capacity Up to 175 lbs.

- Double Ball Bearing Raceway
- Zinc Plated
- Available with Chrome Plated Finish
- Available in 304 Stainless Steel

OPTIONS

- Chrome Plated (**CR**)
- 304 Stainless Steel (**SS**)
- Available in **Plate, Hole or Stem** type



PLATES

Plate	Size	Bolt Pattern	Mounting Bolt
P1	2-3/8" x 3-5/8"	1-3/4" x 2-7/8" to 3"	5/16"

HOLE TYPE / STEM TYPE

Hole	Size	Stem Type
H1/2	1/2	Hollow Kingpin
H10.2	10.2 mm	Hollow Kingpin

Stem	Size	Stem Type
TS43	1/2" x 1"	Thread Stem

Any size stem available.

CASTER SPECIFICATIONS

Wheel Dia. (in.)	Tread Width (in.)	Wheel Type	Capacity (lb)	OAH	Radius	Bearing	Swivel Part #	Rigid Part #
2-1/2	1	PU / Polyolefin	110	3-1/2	2-1/2~	Dbf Flange Ball	1E-07-PP-FB-2510-S-**	1E-07-PP-FB-2510-R-**
3	1	PU / Polyolefin	150	4-1/8	2-3/4~	Precision Ball	1E-07-PP-PB-0310-S-**	1E-07-PP-PB-0310-R-**
3	1	Thermoplastic Rubber	130	4-1/8	2-3/4~	Precision Ball	1E-07-TPR-PB-0310-S-**	1E-07-TPR-PB-0310-R-**
4	1	PU / Polyolefin	175	5-1/4	3-1/4~	Precision Ball	1E-07-PP-PB-0410-S-**	1E-07-PP-PB-0410-R-**
4	1	Duratek Rubber	150	5-1/4	3-1/4~	Precision Ball	1E-07-DR-PB-0410-S-**	1E-07-DR-PB-0410-R-**

~ TL Radius = 3-1/2

* Add **PLATE** size to part number.

** Add **STEM** size to part number.