



# DABE100

## SERIES



Swivel Head Section



Wheel Face Brake



Directional Lock

### **25,000 Lbs. Load Capacity Forged Precision Bearing Casters**

Extra Heavy Fabricated Steel Top Plate and Fork Base

Combination of Heavy duty opposed Spherical Roller Thrust Bearings in the Swivel Head allows this caster to swivel easily even under the most punishing conditions.

Totally Sealed Swivel Head with grease nipple

1-1/2" Wheel Axle

Finish : Black Polymer Color coated










Options : 4 way directional Lock

Wheel Face Break

## DABE100' SERIES CASTERS WITH 'SAS' SERIES HIGH LOAD POLYURETHANE WHEELS

- High Load Capacity Liquid Cast Premium Polyurethane Wheels 93 ± 3 Shore A
- Polyurethane firmly bonded to precision machined Cast Iron Core
- Low rolling resistance; Smooth and Noiseless running.
- Non-Marking and floor protective.
- High Abrasion, Cut and Tear resistant
- 100% tested and guaranteed against Bond Failures.
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range: -40° F to +180° F



Part No. Swivel Castor	Part No. Rigid Castor	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
								
DABE100-165S-SAS	DABE100-163R-SAS	450 x 125 x 2	570	350	365 Dia	4 Holes At 300 p.c.d.	24	11500