

FEATURES

Load Capacity Up to 200 lbs.

- Double Ball Bearing Raceway
- Zinc Plated

OPTIONS***

- Side Lock Brake (SLB)



STEMS**

Stem	Size	Stem Type
TS43	1/2" x 1-1/2"	Threaded Stem
PT58	3/4" x 1"	Pipe Thread
GR72	7/16" x 1-3/8"	Grip Ring Stem
GR74	7/16" x 2"	Grip Ring Stem

PLATE AVAILABLE

Plate	Size	Bolt Pattern	Mounting Bolt
P1	2-3/8" x 3-5/8"	1-3/4" x 2-7/8" to 3"	5/16"

CASTER SPECIFICATIONS

Wheel Dia. (in.)	Tread Width (in.)	Wheel Type	Capacity (lb)	Swivel			Swivel Part #	Rigid Part #
				OAH	Radius	Bearing		
3	1	Hard Rubber	150	3-5/8	2-3/4	Plain Bore	1E-06-HR-PB-0310-S-**	1E-06-HR-PB-0310-R-**
3	1	Thermoplastic Rubber	130	3-5/8	2-3/4	Plain Bore	1E-06-TPR-PB-0310-S-**	1E-06-TPR-PB-0310-R-**
3	1	PU / Polyolefin	150	3-5/8	2-3/4	Plain Bore	1E-06-PB-PB-0310-S-**	1E-06-PB-PB-0310-R-**
3	1	Polyolefin	150	3-5/8	2-3/4	Plain Bore	1E-06-PP-PB-0310-S-**	1E-06-PP-PB-0310-R-**
4	1	Hard Rubber	175	4-5/8	3-3/8	Plain Bore	1E-06-HR-PB-0410-S-**	1E-06-HR-PB-0410-R-**
4	1	Thermoplastic Rubber	145	4-5/8	3-3/8	Plain Bore	1E-06-TPR-PB-0410-S-**	1E-06-TPR-PB-0410-R-**
4	1	PU / Polyolefin	175	4-5/8	3-3/8	Plain Bore	1E-06-PB-PB-0410-S-**	1E-06-PB-PB-0410-R-**
4	1	Polyolefin	175	4-5/8	3-3/8	Plain Bore	1E-06-PP-PB-0410-S-**	1E-06-PP-PB-0410-R-**
5	1	Hard Rubber	200	5-5/8	3-1/2	Plain Bore	1E-06-HR-PB-0510-S-**	1E-06-HR-PB-0510-R-**
5	1	Thermoplastic Rubber	150	5-5/8	3-1/2	Plain Bore	1E-06-TPR-PB-0510-S-**	1E-06-TPR-PB-0510-R-**
5	1	PU / Polyolefin	200	5-5/8	3-1/2	Plain Bore	1E-06-PB-PB-0510-S-**	1E-06-PB-PB-0510-R-**
5	1	Polyolefin	200	5-5/8	3-1/2	Plain Bore	1E-06-PP-PB-0510-S-**	1E-06-PP-PB-0510-R-**

* Add **PLATE** size to part number.

** Add **STEM** size to part number.