

## FEATURES

- Wheel: premium quality designed to eliminate lops and wobble while rolling.
- Finish: bright zinc, brass or chrome plating to resist rust and corrosion.
- Swivel Grease Seal: standard on polished brass models.
- Swivel Construction: double ball bearing.
- Axle: 1/2" diameter.
- King Pin: 5/8" steel rivet, hydraulically upset.
- Zerk Grease Fitting: swivel raceway.
- Fork Leg Spacing: 8" wheel 3". 10" wheel 4".



Polished Brass Caster



Polished Brass with Lock

## CASTER OPTIONS

- VertiLoc Brake: to order, add "VL" to end of model number.

## MOUNTING

Top Plate Size: 4" x 4-1/2"

Bolt Hole Spacing: 2-5/8" x 3-5/8" or 3" x 3"

Mounting Bolt Size: 3/8"



Polished Chrome Caster



Polished Chrome Rigid Caster

## (ZINC PLATED)

Wheel Dia.	Tread Width	Wheel Type	Bearing	Cap.	Swivel Caster Model #	Rigid Caster Model #	Approx. Weight	Load Weight	Swivel Radius
8	2.80/4	Black Pneumatic Rubber	Ball	310	3J-PN-8-W81-940	3J-PN-8-W82-940	8	9-1/2	6-1/8
8	2.80/4	Gray Pneumatic Rubber	Ball	310	3J-PN-8-W81-940G	3J-PN-8-W82-940G	8	9-1/2	6-1/8
10	4.10/4	Black Pneumatic Rubber	Ball	470	3J-PN-10-W87-940	3J-PN-10-W88-940	9	13	7-5/8

## (POLISHED BRASS)

Wheel Dia.	Tread Width	Wheel Type	Bearing	Cap.	Swivel Caster Model #	Rigid Caster Model #	Approx. Weight	Load Weight	Swivel Radius
8	2.80/4	Black Pneumatic Rubber	Ball	310	3J-PN-8-W81-940-1GSPB	3J-PN-8-W82-940-1GSPB	8	9-1/2	6-1/8

## (POLISHED CHROME)

Wheel Dia.	Tread Width	Wheel Type	Bearing	Cap.	Swivel Caster Model #	Rigid Caster Model #	Approx. Weight	Load Weight	Swivel Radius
8	2.80/4	Black Pneumatic Rubber	Ball	310	3J-PN-8-W81-940-1PC	3J-PN-8-W82-940-1PC	8	9-1/2	6-1/8