

# 14

## Scaffolding Casters



Designed for scaffolds. This caster features an easy to engage total locks that locks both wheel and swivel and allow easy locking and repositioning.

### TYPICAL APPLICATIONS

- Scaffolding

### MOUNTING AND SWIVEL CROSS SECTION Standard Plate


Stem length is 37/8". For a more secure installation there are 1/2" cross-drilled holes.

### FEATURES

- **Total Lock Brake:** Easy to engage for swivel and wheels
- **Zerks:** Swivel and hub for easy lubrication
- **Sealed Swivel Section:** Keeps out debris
- **King Bolt:** King bolt and nut construction for added strength

### BEARING

Straight Roller (01)



Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) <small>(Rate for manual operation)</small>	Overall Height (Inches)	Stem Diameter (Inches)	Caster Number
-------------------------	----------------------	--	-------------------------	------------------------	---------------

### Rubber on Iron Core (Roller Bearings)



MR

4	2	350	5	1 1/4	<b>14MR04201SSSC</b>
5	2	450	6	1 1/4	<b>14MR05201SSSC</b>
6	2	500	7 1/4	1 3/8	<b>14MR06201SSSC</b>
8	2	600	9 1/4	1 3/8	<b>14MR08201SSSC</b>

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) <small>(Rate for manual operation)</small>	Overall Height (Inches)	Stem Diameter (Inches)	Caster Number
-------------------------	----------------------	--	-------------------------	------------------------	---------------

### Polyurethane on Iron Core (Roller Bearings)



PI

4	2	700	5	1 1/4	<b>14PI04201SSSC</b>
5	2	800	6	1 1/4	<b>14PI05201SSSC</b>
6	2	800	7 1/4	1 3/8	<b>14PI06201SSSC</b>
8	2	800	9 1/4	1 3/8	<b>14PI08201SSSC</b>