

This lock lets you immobilize equipment in any desired location, but does not interfere with its movement when not in use. Platform trucks, fixture dollies or other castered items can be locked in place by a simple press of the foot. Locking action is created when a large, round friction face of nearly 10 sq. inches in area is pressed against the floor with the force of 70 to 100 lbs. This position lock does not lift equipment.

## FEATURES

**Brake Shoe** - Large, non-skid, molded rubber for solid, no-slip contact

**Foot Pedal** - Adjusted by slight foot pressure for simple, instant locking

**Finish** - Painted



## FLOOR LOCK SPECIFICATIONS

Diameter (in)	Extended Height (in)	Retracted Height (in)	Mounting Plate (in)	Bolt Hole Spacing (in)	Fastener Dia. (in)	Weight (lb)	Part Number
4	5-5/8	5	3-11/16 x 5-3/8	2-5/8 x 3-5/8	3/8	7.75	920FL04548
5	6-1/2	5-7/8	3-11/16 x 5-3/8	2-5/8 x 3-5/8	3/8	8	930FL05650
5	7-9/32	6-21/32	3-11/16 x 5-3/8	2-5/8 x 3-5/8	3/8	8.25	930FL05728
5	7-5/8	6-1/2	4-1/2 x 6	2-7/16 x 4-15/16	1/2	10.25	930FL05762
6	7-3/8	6-3/4	3-11/16 x 5-3/8	2-5/8 x 3-5/8	3/8	8.25	940FL06737
6	7-1/2	6-7/8	3-11/16 x 5-3/8	2-5/8 x 3-5/8	3/8	8.25	940FL06750
6	7-1/2	6-3/8	4-1/2 x 6	2-7/16 x 4-15/16	1/2	10.5	940FL06751
6	7-25/32	6-21/32	4-1/2 x 6	2-7/16 x 4-15/16	1/2	10.5	940FL06778
6	8-1/8	7	4-1/2 x 6	2-7/16 x 4-15/16	1/2	10.5	940FL06812
8	9-1/2	8-3/8	4-1/2 x 6	2-7/16 x 4-15/16	1/2	10.5	950FL08950
8	9-1/2	8-7/8	3-11/16 x 5-3/8	2-5/8 x 3-5/8	3/8	9.5	950FL08951
8	9-7/8	8-3/4	4-1/2 x 6	2-7/16 x 4-15/16	1/2	10.5	950FL08987
8	10-5/16	9-3/16	5-3/8 x 7-1/4	3-3/8 x 5-1/4	1/2	15	950FL081031
8	10-1/2	9-5/8	5-3/8 x 7-1/4	3-3/8 x 5-1/4	1/2	15.25	950FL081050
10	11-1/2	10-3/8	4-1/2 x 6	2-7/16 x 4-15/16	1/2	11.5	980FL101150
10	12-1/2	11-3/8	5-3/8 x 7-1/4	3-3/8 x 5-1/4	1/2	15.25	980FL101250
10	12-3/4	11-7/8	5-3/8 x 7-1/4	3-3/8 x 5-1/4	1/2	15.5	980FL101275