

## Side Winding Caster Jack – JC-SW Series

### 750KG - 1000KG Capacity

Height Adjustable Jacking Castors -  
Polyurethane on Cast Iron Wheels

### FEATURES

- Side Mounting Plate-type Rig
- Vertical (side) and Horizontal (top) wind models
- Vertical (side) and Horizontal (top) wind models
- Up to 76mm - 100mm of lift (travel)
- All Steel Construction
- Premium Polyurethane on cast iron wheel - 93 Shore A (plus,minus3)
- Non-marking, quiet running, abrasion/cut/tear resistant
- Sealed precision ball bearings/low rolling resistance
- Temperature range -20 Deg C to +85 Deg C



Part No.	Wheel Dia x Tread Width	Wheel Material	Fully Extended Height (mm)	Retracted Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
JC-SW-SAS-6	150 x 50	Polyurethane	820	620	135	150 x 100	110 x 60	12	750
JC-SW-SAS-8	200 x 50	Polyurethane	864	664	165				1000
JC-SW-MCI-6	150 x 50	Cast Iron	820	620	135				1000
JC-SW-MCI-8	200 x 50	Cast Iron	864	664	165				1000