

3J-61 / 3J-62 Series Casters

3J-61 SERIES

Load Capacity Up to 500 lbs

- Finish: bright zinc plating to resist rust and corrosion.
- Design: fork legs formed from 3/16" thick steel.
- Swivel Construction: double ball bearing with hardened raceways.
- Axle: 1/2" diameter with zerk grease fitting.
- King Pin: 5/8" steel rivet, hydraulically upset.
- Zerk Grease Fitting: swivel raceway
- Fork Leg Spacing: 2".



CASTER OPTIONS:

- **VertiLoc® Brake:** to order, add "VL" to end of model number.
- **Swivel Lock / Bolt-On:** Field installable 4-position swivel lock. To order specify swivel lock number 3091-22.
- **Swivel Grease Seal:** To order, add "GS" to end of model number.

MOUNTING OPTIONS

Standard Stem Sizes: to order, specify stem code number and add to end of caster model number

Top Plate Size	Bolt Hole Spacing	Mounting Bolt Size
4" x 4 -1/2"	2-5/8" x 3-5/8" to 3" x 3"	3/8"

3J-61 SERIES SPECIFICATIONS

Wheel Diameter	Tread Width	Wheel Type	Bearing	Capacity	Swivel Caster Model Number	Rigid Caster Model Number	Approx. Weight	Load Height	Swivel Radius
4	1-5/8	Cushion / Solid Rubber	Sintered	225	3J-4-61-109	3J-4-62-109	4	5-5/8	3-9/16
		Cushion / Solid Rubber	Roller	225	3J-4-61-209	3J-4-62-209	4	5-5/8	3-9/16
		Hard / Solid Rubber	Sintered	350	3J-4-61-110	3J-4-62-110	4	5-5/8	3-9/16
		Hard / Solid Rubber	Roller	350	3J-4-61-210	3J-4-62-210	4	5-5/8	3-9/16
4	1-1/2	Moldon Rubber / Aluminum Core	Ball	225	3J-4-61-615	3J-4-62-615	5	5-5/8	3-9/16
		Moldon Polyurethane / Aluminum Core	Ball	425	3J-4-61-715	3J-4-62-715	5	5-5/8	3-9/16
		Polyolefin	Plain	450	3J-4-61-521	3J-4-62-521	5	5-5/8	3-9/16
		Polyolefin	Roller	450	3J-4-61-522	3J-4-62-522	5	5-5/8	3-9/16
		Phenolic	Plain	500	3J-4-61-121	3J-4-62-121	4	5-5/8	3-9/16
		Phenolic	Roller	500	3J-4-61-221	3J-4-62-221	4	5-5/8	3-9/16
		5	1-5/8	Cushion / Solid Rubber	Sintered	260	3J-5-61-109	3J-5-62-109	5
Cushion / Solid Rubber	Roller			260	3J-5-61-209	3J-5-62-209	5	6-1/2	4-5/16
Hard / Solid Rubber	Sintered			400	3J-5-61-110	3J-5-62-110	5	6-1/2	4-5/16
Hard / Solid Rubber	Roller			400	3J-5-61-210	3J-5-62-210	5	6-1/2	4-5/16
5	1-1/2	Moldon Rubber / Aluminum Core	Ball	250	3J-5-61-615	3J-5-62-615	6	6-1/2	4-5/16
		Advantage TPR / Flat	Roller	350	3J-5-61-215GF	3J-5-62-215GF	6	6-1/2	4-5/16
		Polyolefin	Plain	450	3J-5-61-521	3J-5-62-521	5	6-1/2	4-5/16
		Polyolefin	Roller	450	3J-5-61-522	3J-5-62-522	5	6-1/2	4-5/16
		Moldon Polyurethane / Aluminum Core	Ball	450	3J-5-61-715	3J-5-62-715	6	6-1/2	4-5/16
		PolyLoc / Grey	Roller	500	3J-5-61-215G	3J-5-62-215G	5	6-1/2	4-5/16
		PolyLoc / Blue	Roller	500	3J-5-61-215P	3J-5-62-215P	5	6-1/2	4-5/16
		Phenolic	Plain	500	3J-5-61-121	3J-5-62-121	5	6-1/2	4-5/16
		Phenolic	Roller	500	3J-5-61-221	3J-5-62-221	5	6-1/2	4-5/16

Continued on next page...

3J-61 / 3J-62 Series Casters

3J-61 SERIES SPECIFICATIONS CONTINUED...

Wheel Diameter	Tread Width	Wheel Type	Bearing	Capacity	Swivel Caster Model Number	Rigid Caster Model Number	Approx. Weight	Load Height	Swivel Radius
6	1-1/2	PolyLoc / Grey	Roller	300	3J-6-61-215G	3J-6-62-215G	6	7-1/2	5-1/16
6	1-1/2	Moldon Rubber / Aluminum Core	Ball	350	3J-6-61-615	3J-6-62-615	7	7-1/2	5-1/16
6	1-1/2	Advantage TPR / Flat	Roller	375	3J-6-61-215GF	3J-6-62-215GF	6	7-1/2	5-1/16
6	1-1/2	PolyLoc / Blue	Roller	500	3J-6-61-215P	3J-6-62-215P	6	7-1/2	5-1/16
6	1-1/2	Phenolic	Plain	500	3J-6-61-121	3J-6-62-121	6	7-1/2	5-1/16
6	1-1/2	Phenolic	Roller	500	3J-6-61-221	3J-6-62-221	6	7-1/2	5-1/16
6	1-1/2	Polyolefin	Delrin	500	3J-6-61-523	3J-6-62-523	6	7-1/2	5-1/16
6	1-1/2	Polyolefin	Roller	500	3J-6-61-525	3J-6-62-525	7	7-1/2	5-1/16
6	1-1/2	Moldon Polyurethane / Aluminum Core	Ball	500	3J-6-61-715	3J-6-62-715	7	7-1/2	5-1/16
8	1-1/2	Advantage TPR / Flat	Roller	500	3J-8-61-215GF	3J-8-62-215GF	8	9-1/2	6-1/2
8	1-1/2	PolyLoc / Grey	Roller	500	3J-8-61-215G	3J-8-62-215G	8	9-1/2	6-1/2
8	1-1/2	PolyLoc / Blue	Roller	500	3J-8-61-215P	3J-8-62-215P	8	9-1/2	6-1/2
8	1-1/2	Polyolefin	Delrin	500	3J-8-61-523	3J-8-62-523	8	9-1/2	6-1/2
8	1-1/2	Polyolefin	Roller	500	3J-8-61-525	3J-8-62-525	8	9-1/2	6-1/2