

FEATURES

Load Capacity Up to 20,000 lbs.

- Top Plate: 1/2" AISI 1045 steel one piece forged, precision welded and through hardened for long life.
- Yoke Base: Notched AISI 1045 steel machined and through hardened to minimize ball indentation and wear.
- Swivel Section: 7" Diameter with 3/4" hard chrome balls in precision machined through hardened raceway with threaded ball plug.
- Legs: 1/2" x 4" steel welded to yoke base using 100,000 psi weld filler, welded inside and outside for superior strength.
- Wheel Axle: 1-1/4" dia. zerk axle with lock nut
- Lubrication: Zerk fitting in swivel section and in recessed head of hollow axle.
- Finish: Zinc plated for greater corrosion resistance.




RIG OPTIONS

- NS** Sealed Swivel Section
SLW Swivel Lock-Welded
SLFI Swivel Lock-Field Installable

BRAKE OPTIONS

- PCB** Poly Cam Brake
FCB Face Contact Brake

SWIVEL CROSS SECTION



MOUNTING PLATE (SWIVEL / RIGID)

Top Plate	Plate Size	Bolt Hole Spacing	Bolt Size
95	8 1/2" x 8 1/2"	7 x 7"	5/8"

SPECIFICATIONS

Wheel Type (Wheel Code)	Dia. (in.)	Width (in.)	Capacity (lbs.)	OAH (in.)	Swl. Lead (in.)	Wt. (lbs.)	Swivel Part Number Add B, P, PL, R or T*
FORGED STEEL (FS) WHEELS WITH ROLLER OR TAPERED BEARINGS							
	6	3	10000	8-1/2	2-1/4	59-1/2	9-95KHD-FS-T-0630-S
	8	4	10000	11	2-1/4	72-1/2	9-95KHD-FS-T-0840-S
	10	3	6500	13	2-1/2	78-1/2	9-95KHD-FS-T-1030-S
	10	4	10000	13	2-1/2	86-1/2	9-95KHD-FS-T-1040-S
FORGED STEEL / V-GROOVED (FS/VG) WHEELS WITH ROLLER BEARINGS							
	6	3	6000	8-1/2	2-1/4	59-1/2	9-95KHD-FS/VG-R-0630-S
	8	4	8350	11	2-1/4	61-1/2	9-95KHD-FS/VG-R-0840-S
	10	3	6000	13	2-1/2	67-3/4	9-95KHD-FS/VG-R-1030-S
	10	4	8350	13	2-1/2	89-1/2	9-95KHD-FS/VG-R-1040-S
LARGE BORE FORGED STEEL (FH) WHEELS WITH ROLLER BEARINGS							
	6	3	17000	8-1/2	2-1/4	59-1/2	9-95KHD-FH-R-0630-S
	8	4	17000	11	2-1/4	72-1/2	9-95KHD-FH-R-0840-S
	10	4	17000	13	2-1/2	86-1/2	9-95KHD-FH-R-1040-S
LARGE BORE FORGED STEEL / V-GROOVED (FH/VG) WHEELS WITH ROLLER BEARINGS							
	8	4	15000	11	2-1/4	61-1/2	9-95KHD-FH/VG-R-0840-S
	10	4	15000	13	2-1/2	86-1/2	9-95KHD-FH/VG-R-1040-S
DUCTILE IRON / CROWNED TREAD (DU/CT) WHEELS WITH ROLLER BEARINGS							
	6	2-1/2	3500	8-1/2	2-1/4	58	9-95KHD-DU/CT-R-0625-S
	6	3	6000	8-1/2	2-1/4	60	9-95KHD-DU/CT-R-0630-S
	8	3	6000	11	2-1/4	64	9-95KHD-DU/CT-R-0830-S
	10	3	6000	13	2-1/2	74	9-95KHD-DU/CT-R-1030-S
DUCTILE IRON (DU) WHEELS WITH ROLLER BEARINGS							
	12	3-1/2	6000	15-1/2	2-1/2	83-1/2	9-95KHD-DU-R-0520-S
NYLACRON™ MD (NY/MD) WHEELS WITH PRECISION BALL BEARINGS							
	6	2-1/2	10,000	8-1/2	2-1/4	36	9-95KHD-NY/MD-P-0625-S
	6	3	10,000	8-1/2	2-1/4	37-1/4	9-95KHD-NY/MD-P-0660-S
	8	3	10,000	11	2-1/4	41	9-95KHD-NY/MD-P-0860-S
	8	4	15,000	11	2-1/2	63	9-95KHD-NY/MD-P-0840-S
	8	6	7200	11	2-1/2	54	9-95KHD-NY/MD-P-0860-S
	10	3	10,000	13	2-1/2	45-1/2	9-95KHD-NY/MD-P-1060-S
	10	4	15,000	13	2-1/2	71	9-95KHD-NY/MD-P-1040-S
	10	5	20,000	13	2-1/2	82	9-95KHD-NY/MD-P-1050-S
	10	6	20,000	13	2-1/2	61-1/4	9-95KHD-NY/MD-P-1060-S
	12	3-1/2	10,000	15-1/2	2-1/2	73-1/2	9-95KHD-NY/MD-P-1235-S
	12	4	15,000	15-1/2	2-1/2	76-1/4	9-95KHD-NY/MD-P-1240-S
	12	5	20,000	15-1/2	2-1/2	90	9-95KHD-NY/MD-P-1250-S
	16	4	15,000	19	3	111-1/2	9-95KHD-NY/MD-P-1640-S
	16	5	20,000	19	3	126-1/4	9-95KHD-NY/MD-P-1650-S
LAMINATED PHENOLIC / TEXITE (TL) WHEELS WITH ROLLER BEARINGS							
	6	5	8000	8-1/2	2-1/4	49	9-95KHD-TL-R-0650-S
	8	6	5000	11	2-1/2	54	9-95KHD-TL-R-0860-S
	10	6	5800	13	2-1/2	61-1/4	9-95KHD-TL-R-1060-S
	12	3-1/2	4000	15-1/2	2-1/2	58-3/4	9-95KHD-TL-R-1235-S
	16	4	8000	19	3	79-3/4	9-95KHD-TL-R-1640-S
PHENOLIC / TEXITE (TM) WHEELS WITH ROLLER BEARINGS							
	8	6	5000	11	2-1/2	54-1/2	9-95KHD-TM-R-0860-S
	10	6	5800	13	2-1/2	54	9-95KHD-TM-R-1060-S
	12	4	8000	15-1/2	2-1/2	67-1/2	9-95KHD-TM-R-1240-S
POLYURETHANE / CAST IRON CORE (PY/CA) WHEELS WITH PRECISION BALL BEARINGS							
	8	4	3500	11	2-1/2	63	9-95KHD-PY/CA-P-0840-S
	10	4	4200	13	2-1/2	71	9-95KHD-PY/CA-P-1040-S
	10	5	5000	13	2-1/2	82	9-95KHD-PY/CA-P-1050-S
	12	3-1/2	4100	15-1/2	2-1/2	73-1/2	9-95KHD-PY/CA-P-1235-S
	12	4	4800	15-1/2	2-1/2	76-1/4	9-95KHD-PY/CA-P-1240-S
	12	5	6000	15-1/2	2-1/2	90	9-95KHD-PY/CA-P-1250-S
	16	4	5970	19	3	111-1/2	9-95KHD-PY/CA-P-1640-S
	16	5	7700	19	3	126-1/4	9-95KHD-PY/CA-P-1650-S

(Continued on Next Page)