WEIGHT ACTUATED LOCKSTEP LADDERS

Think Safety... Buy Weight Actuated!

Single pedal lifts ladder into rolling position.



Apply 70 pounds of pressure to the steps and the ladder automatically drops the front feet to the ground securing the ladder to the floor for safe climbing.



The most durable lock step on the market today! Designed using finite element analysis and then robotically tested. Prototype units achieved more than 60,000 cycles before replacing latch hook. Then 60,000 more cycles.



Features:

- This state of the art lockstep has only one pedal which lifts the ladder into the rolling position
- Climb the ladder and your weight activates the lockstep – locking the ladder to the floor in the climbing position
- 450 lbs. capacity
- Available in both 59° Ladder Slope or 50° Stairway Slope
- 14" deep top step standard 21" and 28" available
- Durable-manufactured with 1"OD tubing
- Built to OSHA and ANSI standards
- Gray powdercoat finish
- CAL OSHA available



Weight Actuated Lock Step

Total Number	Height Inches		59° Ladder Slope	59° Ladder Base	Weight	59° Model# All	50° Stairway	50° Ladder Base	Weight
of Steps	Top Step	Over All	Model#	W" x L"	Lbs	Directional Option	Slope Model#	W" x L"	Lbs
16" WIDE STEP									
5 STEP	50	83	WA052414	24 x 43	91	WA-AD-052414	WA-SW-052414	24 x 50	96
6 STEP	60	93	WA062414	24 x 49	100	WA-AD-062414	WA-SW-062414	24 x 58	109
7 STEP	70	103	WA072414	24 x 55	109	WA-AD-072414	WA-SW-072414	24 x 66	122
8 STEP	80	113	WA082414	24 x 61	127	WA-AD-082414	WA-SW-082414	24 x 74	135
24" WIDE STEP									
5 STEP	50	83	WA053214	32 x 43	110	WA-AD-053214	WA-SW-053214	32 x 50	115
6 STEP	60	93	WA063214	32 x 49	122	WA-AD-063214	WA-SW-063214	32 x 58	120
7 STEP	70	103	WA073214	32 x 55	143	WA-AD-073214	WA-SW-073214	32 x 66	139
8 STEP	80	113	WA083214	32 x 61	160	WA-AD-083214	WA-SW-083214	32 x 74	165
9 STEP	90	123	WA093214	32 x 68	175	WA-AD-093214	WA-SW-093214	32 x 82	180
10 STEP	100	133	WA103214	32 x 74	193	WA-AD-103214	WA-SW-103214	32 x 90	200
11 STEP	110	143	WA113214	32 x 80	205	WA-AD-113214	WA-SW-113214	32 x 98	210
12 STEP	120	153	WA123214	32 x 87	220	WA-AD-123214	WA-SW-123214	32 x 106	230
13 STEP	130	172	WA134014	40 x 94	250	WA-AD-134014	n/a	n/a	n/a
14 STEP	140	182	WA144014	40 x 100	280	WA-AD-144014	n/a	n/a	n/a
15 STEP	150	192	WA154014	40 x 106	310	WA-AD-154014	n/a	n/a	n/a

TREAD TYPES AVAILABLE:

(X) Expanded Metal - Standard • (P) Perforated • (R) Abrasive Mat • (G) Heavy Duty Serrated Grating PLEASE SPECIFY WHEN ORDERING

Product Specifications are subject to change without notice. Please confirm critical specifications.

Ship Prepaid and Add to take advantage of freight cost reductions with our carrier.

Ladder Inspection Procedure

Shipments are made FOB factory. Each product has been inspected before shipment. Consignee is responsible to inspect material at time of delivery, and should refuse shipment or make written notice to carrier upon receipt of damaged materials.

Carriers and Ballymore will not accept claims if damage is not noted at the time of delivery.

Freight Ballymore can provide estimated freight cost based on our preferred carriers. Note: Costs are subject to change depending on fuel surcharges, special delivery requirements, etc. Ballymore will not be responsible for differences in freight estimates and actual freight costs.

On collect or 3rd party billing shipments, any freight claims must be handled by the customer, including refused shipments.